

VHF TETRODE

FU720F

PEAK-OF-SYNC OUTPUT POWER IN COMBINED AMPLIFICATION:

1.36 KW

PEAK-OF-SYNC OUTPUT POWER IN VISION CARRIER AMPLIFICATION:

2.72 KW

GENERAL CHARACTERISTICS

Cathode	Thoriated tungsten
Heating	Direct, DC single phase AC
Filament voltage	4V $\pm$ 5%
Filament current	78A
Interelectrode capacitances, approx.:	
Cathode-control grid	54pF
Control grid-screen grid	95 pF
Screen grid-anode	14 pF
Transconductance ($I_a=1.6A$, $U_{g2}=500V$)	70mA/V
Internal amplification factor, average	11
Operating position	Vertical, anode up or down
Weight, approx.	2.7 kg
Dimensions	See page 95
Anode cooling(1)	Forced air
Air flow, min.	4500L/min
Air pressure, min.	400Pa
Temperature on tube surface, max.	250°C
(1) Values for cooling given for maximum anode dissipation	



TYPICAL OPERATION

		Combined Service	Vision only
Frequency	[MHz]	220	220
Peak-of-sync output power	[kW]	1.36	2.72
Bandwidth(-1dB)	[MHz]	8	6
Gain	[dB]	15	15
Anode voltage	[kV]	2.5	3.0
Control-grid bias voltage	[V]	-40	-40
Screen-grid voltage	[V]	500	500
Anode current(with signal)	[A]	1.11	1.6
Anode current(at zero signal)	[A]	0.5	0.5

MAXIMUM RATINGS

Frequency	250MHz
Anode voltage	5kV
Anode current	2.4A
Control-grid voltage	-500V
Screen-grid voltage	1kV
Anode dissipation	3.5kW
Control-grid dissipation	20W
Screen-grid dissipation	50W

