

UHF TETRODE

YL1057

PEAK-OF-SYNC OUTPUT POWER IN COMBINED AMPLIFICATION:

1.1 kW

OUTPUT POWER IN SOUND CARRIER AMPLIFICATION:

2.3 kW

GENERAL CHARACTERISTICS

Cathode	Oxide
Heating	Indirect
Filament voltage	3.8V
Filament current	20.5A
Interelectrode capacitances, approx:	
Cathode-control grid	42pF
Cathode-screen grid	2.2pF
Cathode-anode	0.005pF
Cathode grid-screen grid	60pF
Cathode grid-anode	0.05pF
Screen-grid-anode	8.2pF
Transconductance ($I_a=0.5A$, $U_{g2}=500V$, $U_a=3kV$)	55mA/V
Internal amplification factor, average	11
Operating position	Any
Weight, approx	1.1kg
Dimensions	See page 94
Anode cooling ⁽¹⁾	Forced air
Air flow, min,	2100L/min
Corresponding pressure drop	220°C
Temperature at air outlet, max,	100°C
Cooling at the sealing between electrode terminal and ceramic	Forced air
Temperature on tube surface, max,	250°C
⁽¹⁾ Values for cooling given for maximum anode dissipation	



MAXIMUM RATINGS

Frequency	1215MHz
Anode voltage(band III)	4.2V
Anode current	1, 2A
Control-grid voltage	-100W
Screen-grid voltage	650V
Anode dissipation	2kW
Control-grid dissipation	5W
Screen -grid dissipation	30W

TYPICAL OPERATION

		Combined Service	Sound only
Frequency	[MHz]	600-860	600-860
Peak-of-sync output power	[kW]	1.1	1.3
Bandwidth (-1dB)	[MHz]	8	6 (-3dB)
Intermodulation distortion	[dB]	≤ -47	-
Gain	[dB]	≥ 16.5	≥ 17.5
Anode voltage	[KV]	3.4	3.4
Screen-grid voltage	[V]	600	600
Anode current (with signal)	[mA]	750	900
Anode current (at zero signal)	[mA]	500	450
Screen-grid current	[mA]	15	22

